

Important Design Parameters


Allow a <u>minimum</u> air space of 15mm all round for easy slide in under counter.

Warning

Ideally the electrical socket fitted in the counter would be recessed

Be aware allowances must be made for any protuding power outlets etc.

Also suitable for a counter set at 850mm high



1198 1023 POWER CABLE ENTRY POINT

Versigen Specification

Dry Heat

Fan Assisted Hotcupboard

_ D<u>imensions</u>

Width - 1198mm

Depth - 660mm

Height - 550mm

Weight - 49kg

Capacity [usable inside space]

Width - 1023mm

Depth - 545mm

Height - 306mm

Power Rating

1.5kw

complete with a 2m long cord set &~10 amp~plug Removable Fan heating System Sahara Fan Model SF315

Materials

1.2mm 304 Grade St/ Steel Top & Supports
0.7mm 430 Grade St/ Steel Internal Structure
GN 1/1 Grid Shelves with 30mm x 30mm tube supports

Installation

RollUnder

All swivel castors, two braked

Minimum Under Counter Void Space

Dimensions

Width - 1228mm

Depth - 675mm

Height - 565mm

ALL SHEET METAL DIMENSIONS ARE I/S (INSIDE SIZES) (UNLESS OTHERWISE STATED) A	LL DIMENSIONS IN (mm), TOLERANCE = LINEAR \pm 0.5mm, ANGULAR \pm 0.5mm (OR AS STATED). ALL SHARP EDGES TO BE REMOVED FROM SHEET METAL PARTS

Product	ROLL UNDER H	OTCUPBOAR	RD	Product No	N/A	No reproduction or p may be made, and no a		Manainan		_	
Description	HC3RU					or assembled in accordance with this drawing without prior written consent. This prohibition is a term of any contract relating to this drawing. Rights reserved		Versigen		1	
Material/Finish		Thickness		Desp/Date			1956 as ammended by the yright Act 1968.	FOODSERVICE EQUIPMENT			
Legacy P/N		Weight	49kg	Quote No.		Dwg No.	CTRP-0	78307	Issue		
Client				SO Number	STD	Drawn By	N.Ra	ymen	_		
Client Project	roject Approved By					Date	25/08	/2020] -		
VERSIGEN AUSTRALIA PTY LTD, 182 HARTLEY ROAD, SMEATON GRANGE, NSW 2567, T: +61 (0)131 653 330, E: sales@versigen.com.au, Web: www.versigen.com.au						Scale	1:20	Sheet	1/2	A4	